

## HEALTH TEST REPORT

For

Shenzhen Sonoff Technologies Co., Ltd.

Wi-Fi Smart Switch with Energy Monitoring

Test Model: POWR3

Additional Model No.: N/A

Prepared for : Shenzhen Sonoff Technologies Co., Ltd.  
Address : 1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : April 15, 2021  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : April 15, 2021 ~ April 23, 2021  
Date of Report : April 25, 2021



**HEALTH TEST REPORT****EN IEC 62311: 2020**

Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

**Report Reference No.** ..... : **LCS210415071AEC**

**Date of Issue** ..... : April 25, 2021

**Testing Laboratory Name** ..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

**Address** ..... : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

**Testing Location/ Procedure** ..... : Full application of Harmonised standards ☒  
Partial application of Harmonised standards ☐  
Other standard testing method ☐

**Applicant's Name** ..... : **Shenzhen Sonoff Technologies Co., Ltd.**

**Address** ..... : 1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

**Test Specification**

**Standard** ..... : EN IEC 62311: 2020

**Test Report Form No.** ..... : LCSEMC-1.0

**TRF Originator** ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

**Master TRF** ..... : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description** ..... : Wi-Fi Smart Switch with Energy Monitoring

**Trade Mark** ..... : SONOFF

**Test Model** ..... : POWR3

**Ratings** ..... : Input: AC 100-240V, 50/60Hz

**Result** ..... : **Positive**

**Compiled by:**

*Linda He*

Linda He/ File administrators

**Supervised by:**

*Jin Wang*

Jin Wang/ Technique principal

**Approved by:**



Gavin Liang/ Manager

**HEALTH --TEST REPORT****Test Report No. : LCS210415071AEC**April 25, 2021  
Date of issue

Test Model ..... : POWR3

EUT..... : Wi-Fi Smart Switch with Energy Monitoring

**Applicant..... : Shenzhen Sonoff Technologies Co., Ltd.**

Address..... : 1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Telephone..... : /

Fax..... : /

**Manufacturer..... : Shenzhen Sonoff Technologies Co., Ltd.**

Address..... : 1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Telephone..... : /

Fax..... : /

**Factory..... : /**

Address..... : /

Telephone..... : /

Fax..... : /

**Test Result****Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

| Revision | Issue Date     | Revisions     | Revised By  |
|----------|----------------|---------------|-------------|
| 000      | April 25, 2021 | Initial Issue | Gavin Liang |
|          |                |               |             |
|          |                |               |             |

## 1. GENERAL INFORMATION

### 1.1. Product Description for Equipment Under Test (EUT)

|                      |  |
|----------------------|--|
| EUT                  | : Wi-Fi Smart Switch with Energy Monitoring    |
| Test Model           | : POWR3  |
| Additional Model No. | : N/A  |
| Model Declaration    | : N/A  |
| Power Supply         | : Input: AC 100-240V, 50/60Hz                  |
| Hardware Version     | : V1.0   |
| Software Version     | : V1.0   |
| WIFI(2.4G Band)      | :  |
| Frequency Range      | : 2412MHz ~ 2472MHz                            |
| Channel Spacing      | : 5MHz   |
| Channel Number       | : 13 Channel for 20MHz bandwidth(2412~2472MHz) |
| Modulation Type      | : 802.11b: DSSS; 802.11g/n: OFDM               |
| Antenna Description  | : PCB Antenna, 1.5dBi(Max.)                    |

## 1.2. Objective

According to its specifications, the EUT must comply with the requirements of the following standards:  
EN IEC 62311: 2020 –Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

## 1.3. Test Methodology

All measurements contained in this report were conducted with EN IEC 62311: 2020.

## 1.4. Facilities

All measurement facilities used to collect the measurement data are located at Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao' an District, Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

## 1.5. Host System Configuration List and Details

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| --           | --          | --    | --            | --          |

## 1.6. External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| --                   | --       | --    |

## 1.7. Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 1.8. Laboratory Accreditations And Listings

### Site Description

EMC Lab. : NVLAP Accreditation Code is 600167-0.  
 FCC Designation Number is CN5024.  
 CAB identifier is CN0071.  
 CNAS Registration Number is L4595.

Name of Firm : Shenzhen LCS Compliance Testing Laboratory Ltd.

Site Location : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

## 1.9. Measurement Uncertainty

| Test Item                     |   | Uncertainty          |
|-------------------------------|---|----------------------|
| Radio Frequency               | : | $0.9 \times 10^{-4}$ |
| Total RF Power, Conducted     | : | 1.0 dB               |
| RF Power Density, Conducted   | : | 1.8 dB               |
| Spurious Emissions, Conducted | : | 1.8 dB               |
| All Emissions, Radiated       | : | 3.1 dB               |
| Temperature                   | : | 0.5 °C               |
| Humidity                      | : | 1 %                  |
| DC And Low Frequency Voltages | : | 1 %                  |

## 2. HUMAN EXPOSURE TO THE ELECTROMAGNETIC FIELDS

### 2.1 Basic Restrictions Reference levels

Council Recommendation 1999/519/EC Annex II

Basic restrictions for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

| Frequency range | Magnetic flux density (mT) | Current density (Ma/m <sup>2</sup> ) (rms) | Whole body average SAR (W/kg) | Localised SAR (head and trunk) (W/kg) | Localised SAR (limbs) (W/kg) | Power density (W/m <sup>2</sup> ) |
|-----------------|----------------------------|--|-------------------------------|---------------------------------------|------------------------------|-----------------------------------|
| 0Hz             | 40                         | -  | -                             | -                                     | -                            | -                                 |
| >0-1Hz          | -                          | 8  | -                             | -                                     | -                            | -                                 |
| 1-4Hz           | -                          | 8/f  | -                             | -                                     | -                            | -                                 |
| 4-1000Hz        | -                          | 2  | -                             | -                                     | -                            | -                                 |
| 1000Hz-100kHz   | -                          | f/500                                      | -                             | -                                     | -                            | -                                 |
| 100kHz-10MHz    | -                          | f/500                                      | 0.08                          | 2                                     | 4                            | -                                 |
| 10MHz-10GHz     | -                          | -  | 0.08                          | 2                                     | 4                            | -                                 |
| 10-300GHz       | -                          | -  | -                             | -                                     | -                            | 10                                |

Note:

1. f is the frequency in Hz.
2. The basic restriction on the current density is intended to protect against acute exposure effects on central nervous system tissues in the head and trunk of the body and includes a safety factor. The basic restrictions for ELF fields are based on established adverse effects on the central nervous system. Such acute effects are essentially instantaneous and there is no scientific justification to modify the basic restrictions for exposure of short duration. However, since the basic restriction refers to adverse effects on the central nervous system, this basic restriction may permit higher current densities in body tissues other than the central nervous system under the same exposure conditions.
3. Because of electrical inhomogeneity of the body, current densities should be averaged over a cross section of 1cm<sup>2</sup> perpendicular to the current direction.
4. For frequencies up to 100 kHz, peak current density values can be obtained by multiplying the rms value by  $\sqrt{2}$ (=1.414). For pulses of duration  $t_p$  the equivalent frequency to apply in the basic restrictions should be calculated as  $f=1/(2t_p)$
5. For frequencies up to 100kHz and for pulsed magnetic fields, the maximum current density associated with the pulses can be calculated from the rise/fall times and the maximum rate of change of magnetic flux density. The induced current density can then be compared with the appropriate basic restriction.
6. All SAR values are to be averaged over any six-minute period.
7. Localised SAR averaging mass is any 10g of contiguous tissue; the maximum SAR so obtained should be the value used for the estimation of exposure. These 10g of tissue are intended to be a mass of contiguous tissue with nearly homogeneous electrical properties. In specifying a contiguous mass of tissue, it is recognised that this concept can be used in computational dosimetry but may present difficulties for direct physical measurements. A simple geometry such as cubic tissue mass can be used provided that the calculated dosimetric quantities have conservation values relative to the exposure guidelines.

8. For pulses of duration  $t_p$  the equivalent frequency to apply in the basic restrictions should be calculated as  $=1/(2t_p)$ . Additionally, for pulsed exposures, in the frequency range 0,3 to 10GHz and for localised exposure of the head, in order to limit and avoid auditory effects caused by thermoelastic expansion, an additional basic restriction is recommended. This is that SA should not exceed 2mJ kg-1 averaged over 10g of tissue.

## 2.2 Reference Levels

Council Recommendation 1999/519/EC Annex II

Basic restrictions for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

| Frequency range | E-field strength (V/m) | H-field strength (A/m)  | B-field (μT)          | Equivalent plane wave power density Seq (W/m2) |
|-----------------|------------------------|-------------------------|-----------------------|--|
| 0-1Hz           | -                      | $3,2 \times 10^4$       | $4 \times 10^4$       | -  |
| 1-8Hz           | 1000                   | $3,2 \times 10^4 / f^2$ | $4 \times 10^4 / f^2$ | -  |
| 8-25Hz          | 1000                   | $4000 / f$              | $5000 / f$            | -  |
| 0.025Hz-0,8kHz  | $250 / f$              | $4 / f$                 | $5 / f$               | -  |
| 0,8-3kHz        | $250 / f$              | 5                       | 6,25                  | -  |
| 3-150kHz        | 87                     | 5                       | 6,25                  | -  |
| 0,15-1MHz       | 87                     | $0,73 / f$              | $0,92 / f$            | -  |
| 1-10MHz         | $87 / f^{1/2}$         | $0,73 / f$              | $0,92 / f$            | -  |
| 10-400MHz       | 28                     | 0.073                   | 0,092                 | 2  |
| 400-2000MHz     | $1,375 f^{1/2}$        | $0,0037 f^{1/2}$        | $0,0046 f^{1/2}$      | $f / 200$                                      |
| 2-300GHz        | 61                     | 0,16                    | 0,20                  | 10   |

Note:

1. f is the frequency in Hz.
2. The basic restriction on the current density is intended to protect against acute exposure effects on central nervous system tissues in the head and trunk of the body and includes a safety factor. The basic restrictions for ELF fields are based on established adverse effects on the central nervous system. Such acute effects are essentially instantaneous and there is no scientific justification to modify the basic restrictions for exposure of short duration. However, since the basic restriction refers to adverse effects on the central nervous system, this basic restriction may permit higher current densities in body tissues other than the central nervous system under the same exposure conditions.
3. Because of electrical inhomogeneity of the body, current densities should be averaged over a cross section of 1cm<sup>2</sup> perpendicular to the current direction.
4. For frequencies up to 100 kHz, peak current density values can be obtained by multiplying the rms value by  $\sqrt{2}$  (=1.414). For pulses of duration  $t_p$  the equivalent frequency to apply in the basic restrictions should be calculated as  $=1/(2t_p)$
5. For frequencies up to 100kHz and for pulsed magnetic fields, the maximum current density associated with the pulses can be calculated from the rise/fall times and the maximum rate of change of magnetic flux density. The induced current density can then be compared with the appropriate basic restriction.
6. All SAR values are to be averaged over any six-minute period.
7. Localised SAR averaging mass is any 10g of contiguous tissue; the maximum SAR so obtained should be the value used for the estimation of exposure. These 10g of tissue are intended to be a mass of contiguous tissue with nearly homogeneous electrical properties. In specifying a contiguous mass of tissue, it is recognised that this concept can be used in computational dosimetry but may present difficulties for direct physical measurements. A simple geometry such as cubic tissue mass can be used

provided that the calculated dosimetric quantities have conservation values relative to the exposure guidelines.

8. For pulses of duration  $t_p$  the equivalent frequency to apply in the basic restrictions should be calculated as  $f = 1/(2t_p)$ . Additionally, for pulsed exposures, in the frequency range 0.3 to 10GHz and for localised exposure of the head, in order to limit and avoid auditory effects caused by thermoelastic expansion, an additional basic restriction is recommended. This is that SA should not exceed 2mJ kg<sup>-1</sup> averaged over 10g of tissue.

#### Classification of the assessment methods

The antenna of the product, under normal use condition is at least 20cm away from the body of the user. Warning statement on the user for keeping 20cm separation distance and the prohibition of operating to a person has been printed on the user manual. So, this product under normal use is located on electromagnetic far field between the human body.

#### Far Field Calculation Formula

$$E = \frac{\sqrt{30 \times G \times TP}}{D}$$

Where

$G$ : numerical gain of transmitting antenna;

$TP$ : Transmitted power in watt;

$D$ : distance from the transmitting antenna in meter.

## 2.3. Test Results

According to the radio test report (LCS210415071AEB):

| Mode      | Output Power To Antenna (dBm) | Antenna Gain (dBi) | Minimum Distance in Meter (m) | E-field Strength (V/m) | E-field Strength Limit (V/m) | Result |
|-----------|-------------------------------|--------------------|-------------------------------|------------------------|------------------------------|--------|
| 2.4G WIFI | 16.37                         | 1.5                | 0.2                           | 6.78                   | 61.00                        | Pass   |

Note:

1. Only record worst case data.
2. All other emissions are too low to read.

This proves that the unit complies with the EN 62311 for RF exposure requirement.

-----THE END OF TEST REPORT-----